

### **INTERACTIVE KIOSK** MODEL 55-BE

# INFORM. ANNOUNCE. COMMUNICATE.

#### **Dynamic Communication**

Out with the old static message panels and in with the new dynamic digital signage! NUMMAX offers an effective multimedia solution that is flexible and economical, an attractive and long lasting cutting-edge communication tool with many advantages! Our very intuitive content management software, Nummax Manager, allows you to upload and modify your displayed content on the fly, instantly grabbing your audience's attention. Optimizing client communication has never been so easy!

Enter the digital signage era with a Nummax, turnkey solution. We specialize in manufacturing, operating and installing all types of digital signage solutions. Nummax ensures outstanding quality and service thanks to our experienced and professional team, our powerful technology and reliable products.

Dynamic digital displays allow you to showcase your products, services and promotions, where you want, when you want!

# ~~~

O

#### EFFICIENT

Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.

#### ATTRACTIVE AND APPEALING

Powerful, responsive communication made possible through real-time broadcasting of messages.



#### ECONOMICAL

Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.

#### SIMPLE, FLEXIBLE BROADCASTING

Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.



## TECHNICAL SPECIFICATIONS

	55.05
Model	55-BE
Screen	55"
Resolution (px)	1920 x 1080
Display Area (W x H)	680 x 1210 mm 26,77 x 47,63 in
Viewing Angle	H178°, V178°
Brightness	2000 cd/m <sup>2</sup>
Contrast Ratio	5000-1
Colours	16.7M
Response Time	5ms
Lifetime	60 000H+
Power	AC-110-240V
Power consumption	100 w
Working temperature	-40/60 °C
Working humidity	10-80%
Heating component	Included
Frame	Aluminium
Orientation	Portrait

Back Frame	Floor standing
Working environment	Exterior
Product size (WxH)	880 x 1930 mm 34,64 x 75,98 in
Warranty (parts & labour)	3 years
Compliance	CE-UL
Glass	Vandal proof
Player	Included
Software	Included
Communication	Wired+wifi
Tactile	Yes
Speaker(s)	Yes
HD Camera	Option
NFC	Option
RFID	Option
Card reader	Option
Wheels	Option
Professional transport case	Option

880 mm 34,64 in



