

LED DIGITAL WINDOW (SIGNAGE) NUMMAX-PRO 5 mm

CAPTURE YOUR CLIENTS' ATTENTION. REEL THEM IN.

Dynamic Communication

Out with the old static message panels and in with the new dynamic digital signage! NUMMAX offers an effective multi-media solution that is flexible and economical, an attractive and long lasting cutting-edge communication tool with many advantages! Our very intuitive content management software, Nummax Manager, allows you to upload and modify your displayed content on the fly, instantly grabbing your audience's attention. Optimizing client communication has never been so easy!

Enter the digital signage era with a Nummax, turnkey solution. We specialize in manufacturing, operating and installing all types of digital signage solutions. Nummax ensures outstanding quality and service thanks to our experienced and professional team, our powerful technology and reliable products.

Dynamic digital displays allow you to showcase your products, services and promotions, where you want, when you want!



ECONOMICAL
Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.



EFFICIENT
Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.



ATTRACTIVE AND APPEALING
Powerful, responsive communication made possible through real-time broadcasting of messages.



SIMPLE, FLEXIBLE BROADCASTING
Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.

TECHNICAL SPECIFICATIONS

Model	Nummax-pro 5 mm
Display Area (WxH)	1280 x 640 mm 50,39 x 25,19 in
Total dimensions (including frame) (WxHxD)	1280 x 640 x 105 mm 50,39 x 25,19 x 4,13 in
Stackable	Yes
LED spacing	5 mm
LED configuration	SMD 3:1
Pixel resolution (px)	256 x 128
Colour capacity	16 bits
Brightness	4500 nits
Light and Temperature sensor	Yes
LED display dimming	256
Refresh rate	2000 Hz +
Frequency	60 Hz +
Colour type	RGB
Viewing distance	5 m
Viewing angle	H140°, V120°
Lifetime	100 000H+

Power	AC-110-240V
Warranty (parts & labour)	3 years
Compliance	CE-UL
Maximum power consumption	656w
Average power consumption	265w
Working temperature	-5/60 °C
Working humidity	10-80%
Working environment	Window interior
Frame	Aluminium
Weight	80 lbs
Orientation	Portrait - landscape
Back Frame	Hanging
Player	Included
Software	Included
Communication	Wired+wifi
Speaker(s)	Option

