



NUMMAX LED DISPLAY

NUMMAX-R5

INFORM. ANNOUNCE. COMMUNICATE.

Dynamic Communication

Out with the old static message panels and in with the new dynamic digital signage! NUMMAX offers an effective multimedia solution that is flexible and economical, an attractive and long lasting cutting-edge communication tool with many advantages! Our very intuitive content management software, Nummax Manager, allows you to upload and modify your displayed content on the fly, instantly grabbing your audience's attention. Optimizing client communication has never been so easy!

Enter the digital signage era with a Nummax, turnkey solution. We specialize in manufacturing, operating and installing all types of digital signage solutions. Nummax ensures outstanding quality and service thanks to our experienced and professional team, our powerful technology and reliable products.

Dynamic digital displays allow you to showcase your products, services and promotions, where you want, when you want!



EFFICIENT

Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.



ECONOMICAL

Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.



ATTRACTIVE AND APPEALING

Powerful, responsive communication made possible through real-time broadcasting of messages.



SIMPLE, FLEXIBLE BROADCASTING

Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.

TECHNICAL SPECIFICATIONS

Indoor						Outdoor		
Pixel Pitch	1.56	1.95	2.604	2.976	3.91	2.604	2.976	3.91
LED Configuration	SMD1212	SMD1515	SMD1515	SMD2020	SMD2020	SMD1415	SMD1415	SMD1921
Density (pixel/m ²)	409600	262144	147456	112896	65536	147456	112896	65536
Brightness	≤800 nits					≥4000 nits		
IP Rating	IP45					IP65		
Cabinet Materiel	Die-casting Aluminum					Die-casting Aluminum		
Scan	40 scan	32 scan	32 scan	21 scan	16 scan	32 scan	21 scan	16 scan
Module Weight	0.5 kg					0.5 kg		
Cabinet Weight	7.5 kg					8 kg		
Module Size	250 x 250 mm					250 x 250 mm		
Cabinet Size	500 x 500 x 85 mm					500 x 500 x 85 mm		
Module Pixel	160 x 160	128 x 128	96 x 96	84 x 84	64 x 64	96 x 96	84 x 84	64 x 64
Cabinet Pixel	320 x 320	256 x 256	192 x 192	168 x 168	128 x 128	192 x 192	168 x 168	128 x 128
Max Power	600 W/m ²					750 W/m ²		
Average Power	360 W/m ²					450 W/m ²		
Viewing Angle	H140°(+70/-70) V140°(+70/-70)					H140°(+70/-70) V140°(+70/-70)		
Control Way	Synchronous / Asynchronous					Synchronous / Asynchronous		
Colour Capacity	16 bit					16 bit		
Signal	AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI					AV, S-Video, VGA, DVI, YPbPr, HDMI, SDI		
Work Humidity	10% ~ 90%					10% ~ 90%		
Work Temperature	-20°C ~ + 65°C					-20°C ~ + 65°C		
Warranty	3 years (parts)					3 years (parts)		

ROLLING CASES • MOUNTING STRUCTURE • CABLES

