



INTERACTIVE KIOSK MODEL 55-BE / 75-BE

INFORM. ANNOUNCE. COMMUNICATE.

Dynamic Communication

Out with the old static message panels and in with the new dynamic digital signage! NUMMAX offers an effective multimedia solution that is flexible and economical, an attractive and long lasting cutting-edge communication tool with many advantages! Our very intuitive content management software, Nummax Manager, allows you to upload and modify your displayed content on the fly, instantly grabbing your audience's attention. Optimizing client communication has never been so easy!


Enter the digital signage era with a Nummax, turnkey solution. We specialize in manufacturing, operating and installing all types of digital signage solutions. Nummax ensures outstanding quality and service thanks to our experienced and professional team, our powerful technology and reliable products.

Dynamic digital displays allow you to showcase your products, services and promotions, where you want, when you want!



EFFICIENT

Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.



ECONOMICAL

Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.



ATTRACTIVE AND APPEALING

Powerful, responsive communication made possible through real-time broadcasting of messages.



SIMPLE, FLEXIBLE BROADCASTING

Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.

TECHNICAL SPECIFICATIONS

Model	55-BE (1F)	55-BE 2F	75-BE (1F)	75-BE 2F
Screen	55"		75"	
Resolution [px]	2160 x 3840 (4K)			
Display Area (W x H)	680 x 1210 mm 26,77 x 47,63 in		928 x 1650 mm 36,53 x 64,96 in	
Viewing Angle	H178°, V178°			
Brightness	3000 cd/m²			
Contrast Ratio	1500-1			
Colours	16,7M			
Response Time	5 ms			
Lifetime	60 000 h+			
Power	AC-110-240 V			
Power Consumption	600 W	1060 W	900 W	1600 W
Working Temperature	-40/60 °C			
Working Humidity	5-90 %			
Heating Component	Included			

Frame	Aluminium powder coating finish			
Weight	168 kg 370 lbs	181 kg 400 lbs	250 kg 551 lbs	270 kg 595 lbs
Orientation	Portrait			
Back Frame	Floor standing			
Working Environnement	Exterior			
Product Size (W x H)	885 x 2090 mm 34,84 x 82,28 in		1220 x 2400 mm 48,03 x 94,48 in	
Warranty (parts & labour)	3 years			
Compliance	CE-UL			
Glass	Vandal proof Tempered glass 8 mm			
Player	Included (Windows or Androir)			
Software	Included			
Communication	Wired + Wifi			
Tactile	Nano touch technology			
Speaker(s)	Yes			
HD Camera	Option			

