



DRIVE-THROUGH KIOSK

MODEL 55-BE-2-SIDE

INFORM. ANNOUNCE. COMMUNICATE.

Dynamic Communication

Out with the old static message panels and in with the new dynamic digital signage! NUMMAX offers an effective multimedia solution that is flexible and economical, an attractive and long lasting cutting-edge communication tool with many advantages! Our very intuitive content management software, Nummax Manager, allows you to upload and modify your displayed content on the fly, instantly grabbing your audience's attention. Optimizing client communication has never been so easy!

Enter the digital signage era with a Nummax, turnkey solution. We specialize in manufacturing, operating and installing all types of digital signage solutions. Nummax ensures outstanding quality and service thanks to our experienced and professional team, our powerful technology and reliable products.

Dynamic digital displays allow you to showcase your products, services and promotions, where you want, when you want!

EFFICIENT



Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.

ECONOMICAL



Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.

ATTRACTIVE AND APPEALING



Powerful, responsive communication made possible through real-time broadcasting of messages.

SIMPLE, FLEXIBLE BROADCASTING



Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.

TECHNICAL SPECIFICATIONS

Model	55-BE-2-SIDE
Screen	2x 55"
Resolution (px)	2160 x 3840 (4K)
Display Area (W x H)	2x 680 x 1210 mm 26,77 x 47,63 in
Viewing Angle	H178°, V178°
Brightness	3800 cd/m ²
Contrast Ratio	1500-1
Colours	16,7M
Response Time	5 ms
Lifetime	60 000 h+
Power	AC-110-240 V
Power Consumption	1200 W
Working Temperature	-40/60 °C
Working Humidity	5-90 %
Heating Component	Included
Frame	Steel powder coating finish
Weight	336 kg 740 lbs
Orientation	Portrait
Back Frame	Floor standing
Working Environment	Exterior
Product Size (W x H)	1500 x 2095 x 150 mm 59,05 x 82,48 x 5,91 in
Warranty (parts & labour)	3 years
Compliance	CE-UL
Glass	Vandal proof Tempered glass 8 mm
Player	Included
Software	Included
Communication	Wired + Wifi

Drive-Thru Kit	<ul style="list-style-type: none"> - UPS (Power unit) - Wireless headset - Outdoor microphone - Front speaker - Motion sensor - Audio filter - Control software
Side Panels	Option

