

DRIVE-THROUGH KIOSK MODEL 55-BE-A / 75-BE-A

COMPLETE VEHICLE DETECTION SYSTEM AND INTERCOM CONTROL KIT

Drive-through service is easier than ever!

Restaurateurs: set up an innovative drive-through system quickly and affordably. The Nummax system includes a display kiosk that will feature your menus according to the time of day, an intercom system that is automatically activated when a vehicle arrives, and a headset for taking orders.

Digital kiosks have a positive impact on your brand image, presenting you as a modern, innovative business.

Simple, intuitive and fun to use, interactive kiosks provide real added value at a trade show or exhibit, in stores, or during promotional events in public spaces.

We have a range of evolving, competitive interactive kiosks to meet all of your interactive dynamic display requirements both indoor and outdoor.



 \mathbf{O}

EFFICIENT

Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.

ATTRACTIVE AND APPEALING

Powerful, responsive communication made possible through real-time broadcasting of messages.



ECONOMICAL

Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.

×

SIMPLE, FLEXIBLE BROADCASTING

Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.



TECHNICAL SPECIFICATIONS

| Model | 55-BE-A | 75-BE-A |
|----------------------|---|---|
| Screen | 55" | 75" |
| Resolution (px) | 3840 x 2160 (4K) | |
| Display Area (W x H) | 680 x 1210 mm (16/9) 26,77 x 47,63 in | 928 x 1650 mm (16/9) 36,53 x 64,96 in |
| Viewing Angle | H178°, V178° | |
| Brightness | 3000 cd/m ² | |
| Contrast Ratio | 1500:1 | |
| Coulours | 16,7M | |
| Response Time | 5 ms | |
| Lifetime | 60 000 h+ | |
| Power | AC-110-240 V | |
| Max consumption | 600 W | 900 W |
| Working temperature | -40/60 °C | |
| Working humidity | 5-90 % | |
| Heating compenent | Inclus | |
| Cadre | Aluminum powder coating finish | |

| Orientation | Portrait | |
|---------------------------|--|---|
| Weight | 168 kg (370 lbs) | 250 kg (551 lbs) |
| Installation | Ground | |
| Working environment | Outdoor | |
| Product size (L x H x P) | 885 x 2090 x 145 mm 34,84 x 82,28 x 5,7 in | 1220 x 2400 x 230 mm 48,03 x 94,48 x 9,05 in |
| Warranty (parts & labour) | 3 ans | |
| Compliance | CEUL | |
| Glass | Vandal proof | |
| Player | Included (Windows) | |
| Software | Included | |
| Communication | Cable+wifi | |
| Drive-thru kit | UPS (Power unit) Wireless headset Outdoor microphone Front speaker Motion sensor Audio filter Control software | |
| Side panels | Option | |



