

JUMBOCUBE NUMMAX-JUMBOCUBE

BROADCAST YOUR MESSAGES TO A LARGE AUDIENCE.



Dynamic Communication

Out with the old static message panels and in with the new dynamic digital signage! NUMMAX offers an effective multi-media solution that is flexible and economical, an attractive and long lasting cutting-edge communication tool with many advantages! Our very intuitive content management software, Nummax Manager, allows you to upload and modify your displayed content on the fly, instantly grabbing your audience's attention. Optimizing client communication has never been so easy!

Enter the digital signage era with a Nummax, turnkey solution. We specialize in manufacturing, operating and installing all types of digital signage solutions. Nummax ensures outstanding quality and service thanks to our experienced and professional team, our powerful technology and reliable products.

Dynamic digital displays allow you to showcase your products, services and promotions, where you want, when you want!



ECONOMICAL

Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.



EFFICIENT

Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.



ATTRACTIVE AND APPEALING

Powerful, responsive communication made possible through real-time broadcasting of messages.



SIMPLE, FLEXIBLE BROADCASTING

Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.

TECHNICAL SPECIFICATIONS

Model	JumboCube	
LED spacing	5.33 mm	6.67 mm
Pixel resolution (px)	480 x 300	384 x 240
Brightness	5000 nits	
Minimum Viewing distance	6 m / 19'	7 m / 23'
Maximum power consumption	13107 W	
Average power consumption	4096 W	
Display Area	4x 2560 x 1600 mm / 100,7 x 63 in	
Total dimensions (including frame)	2560 x 1600 x 2560 mm / 100,7 x 63 x 100,7 in	
LED configuration	SMD 3:1	
Colour capacity	8 bits	
Refresh rate	3840 Hz +	
Frequency	60 Hz +	
Colour type	RGB	
Viewing angle	H140°, V140°	

Lifetime	100 000 H+
Power	AC-110-240 V
Warranty	5 years
Compliance	c ETL us / FCC / Can-ICES-003
Working temperature	-5 / 60 °C / 23 - 140 °F
Working humidity	10-80%
Working environment	Interior
Frame	Aluminum
Weight	680 kg / 1500 lbs
Orientation	Landscape
Player	Windows or Android
Software	Included
Communication	Wired
Suspension cables and anchors	Included
Installation	Included

